

# According to Regulation (EC) No. 1907/2006 (REACH)

www.siriusmarine.co.uk

### **OneShot Diesel Storage Pro**

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

**Product name:** OneShot Diesel Storage Pro

Product code: OS1270SP

**Product description:** Liquid fuel additive.

CAS No.:

EC No.:

Not applicable.

Not applicable.

Not applicable.

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified use(s):** Liquid fuel additive.

**Uses advised against:** Follow supplier's recommendations on correct use of the

product.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Sirius Marine Services Ltd.

Redstone Wharf

Sandy Lane Industrial Estate

Stourport on Severn Worcestershire DY13 9QB

**United Kingdom** 

**Telephone:** 01299 871 048

E-mail: <u>info@siriusmarine.co.uk</u>

Website: www.siriusmarine.co.uk

1.4 Emergency telephone number

**In case of emergency, call:** 07990 848 868 (24 hours, 7 days)



# According to Regulation (EC) No. 1907/2006 (REACH)

www.siriusmarine.co.uk

#### **SECTION 2: Hazard Identification**

#### 2.1 Classification of the substance or mixture

#### 2.1.1. Classification according to Regulation (EC) No. 1272/2008 (CLP)

Acute Tox. 4; H302 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 Carc. 2; H351

Aquatic Chronic 2; H411

#### 2.1.2. Classification according to Directive 67/548/EEC & Directive 1999/45/EC

Harmful; Xn; R20/21/22 Irritant; Xi; R36/38 Carc. Cat. 3; R40 Harmful; Xn; R65

Dangerous for the environment; N; R51/53

#### 2.2 Label elements

#### 2.2.1. Label according to Regulation (EC) No. 1272/2008 (CLP)

#### Hazard pictogram(s):



Signal Word: Danger.

**Hazard Statement(s):** H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H351: Suspected of causing cancer.



### Safety Data Sheet

# According to Regulation (EC) No. 1907/2006 (REACH)

H411: Toxic to aquatic life with long lasting effects.

**Precautionary Statement(s):** P201: Obtain special instructions before use.

P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves / protective clothing / eye

protection / face protection.

P301 + P310: IF SWALLOWED: Immediately call a

POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to: disposal should be in accordance with local, state or national legislation.

**Supplemental Hazard information** None. **(EU):** 

#### 2.2.2. Label according to Directive 67/548/EEC or Directive 1999/45/EC

#### Hazard symbol(s):





**Indication(s) of danger:** Harmful; Dangerous for the Environment.

Risk phrase(s): R20/21/22: Harmful by inhalation, in contact with skin

and if swallowed.

R36/38: Irritating to eyes and skin.

R40: Limited evidence of a carcinogenic effect. R65: Harmful: may cause lung damage if swallowed. R51/53: Toxic to aquatic organisms, may cause long-

term adverse effects in the aquatic environment.

Safety Phrase(s): S1/2: Keep locked up and out of the reach of children.

S23: Do not breathe fumes/vapour.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately

with plenty of water and seek medical advice.

S29: Do not empty into drains.



### Safety Data Sheet

# According to Regulation (EC) No. 1907/2006 (REACH)

S35: This material and its container must be disposed of in a safe way.

S36: Wear suitable protective clothing.

S39: Wear eye/face protection.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special

instructions/Safety Data Sheets.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

#### 2.3 Other hazards

None known.

#### **SECTION 3: Composition**

#### 3.2 Mixtures

#### Classification according to Regulation (EC) No. 1272/2008 (CLP)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Solvent naphtha (petroleum), heavy aromatic	30 - 60	64742-94-5	265-198-5	649-424-00-3	Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 2; H411
Xylene	10 - 30	1330-20-7	215-535-7	601-022-00-9	Flam. Liq. 3, H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332
Amine/aldehyde condensation products	10 - 30	-	-	-	Acute Tox. 4 H302 Skin Irrit. 2; H315 Acute Tox. 4; H312 Eye Irrit. 2; H319 Acute Tox. 4; H332
Trimethylbenzene	5 - 15	25551-13-7	247-099-9	-	Flam. Liq. 3, H226 Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315
Naphthalene	1 - 5	91-20-3	202-049-5	601-052-00-2	Acute Tox. 4; H302 Carc. 2; H351 Aquatic Acute 1; H400 Aquatic Chronic 1; H410



# According to Regulation (EC) No. 1907/2006 (REACH)

#### www.siriusmarine.co.uk

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
3,3'-Methylenebis(5- methyloxazolidine)	≤1	66204-44-2	266-235-8	-	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314

#### Classification according to Directive 67/548/EEC

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Solvent naphtha (petroleum), heavy aromatic	30 - 60	64742-94-5	265-198-5	649-424-00-3	Xi; R36/38 Xn; R65 N; R51/53
Xylene	10 - 30	1330-20-7	215-535-7	601-022-00-9	R10 Xn; R20/21 Xi; R36/38
Amine/aldehyde condensation products	10 - 30	-	-	-	Xn; R20/21/22 Xi; R36/38
Trimethylbenzene	5 - 15	25551-13-7	247-099-9	-	R10 Xn; R21/22 Xi; R38
Naphthalene	1 - 5	91-20-3	202-049-5	601-052-00-2	Xn; R22 Carc. Cat. 3; R40 N; R50/53
3,3-Methylenebis[5-methyloxazolidine]	≤1	66204-44-2	266-235-8	-	Xn; R21/22 C; R34 R52

See Section 16 for full description of R phrases and H statements.

#### **SECTION 4: First Aid Measures**

#### 4.1 Description of first aid measures

**INHALATION:** Obtain immediate medical attention. Remove patient

form exposure, keep warm and at rest.

**SKIN CONTACT:** Remove contaminated clothing immediately. Rinse

affected area with copious amounts of water. Then wash area with soap and water for at least 15 minutes. If symptoms persist, obtain medical attention. Discard of or wash thoroughly contaminated clothing.

**EYE CONTACT:** Remove contact lenses if present and easy to do.

Wash eyes immediately with plenty of water for at least



# Safety Data Sheet

# According to Regulation (EC) No. 1907/2006 (REACH)

15 minutes. Seek medical attention immediately.

**INGESTION:** Provided the patient is conscious wash mouth out with

water and provide patient with 200-300 ml of water to drink. Do not induce vomiting. Obtain medical attention

immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Skin contact causes redness and pain. Eye contact causes watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth, throat and digestive tract. If swallowed, aspiration into lungs may result in chemical pneumonia.

Suspected of causing cancer.

#### 4.3 Indication of any immediate medical attention and special treatments needed:

In case of accident or if you feel unwell, seek medical advice immediately. If swallowed, patient should be monitored for signs of breathing difficulty as effects of aspiration may be delayed for up to 48 hours. If breathing is laboured, oxygen should be administered by qualified personnel.

#### **SECTION 5: Fire-fighting Measures**

#### 5.1 Extinguishing Media

**Suitable extinguishing media:** Foam, CO2 or dry powder.

For large fires, use water.

**Unsuitable extinguishing media:** Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Combustible liquid and vapour. Vapour may form explosive mixture with air. Vapour is heavier than air and may accumulate in confined spaces.

Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, various hydrocarbons and nitrogen oxides.

#### 5.3 Advice for fire-fighters

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire exposed containers cool by spraying with water. Do not allow to enter drains, sewers or watercourses.

Flash point: approx. > 65°C (Closed cup).



# According to Regulation (EC) No. 1907/2006 (REACH)

www.siriusmarine.co.uk

#### **SECTION 6: Accidental Release Measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Eliminate sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Avoid breathing fumes/vapour. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate. (See section 8).

#### 6.1.2 For emergency responders

Keep unnecessary personnel away. Wear suitable protective clothing (See Section 8). Contaminated clothing should be thoroughly cleaned.

#### 6.2 Environmental precautions

Collect spillage. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

#### 6.3 Methods and materials for containment and clearing up

#### 6.3.1 For containment

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

#### 6.3.2 For cleaning up

Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Using non-sparking tools transfer the contaminated absorbent material into a container for disposal. The containers used should be plastic-lined sealable drums. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

#### 6.3.3 Other advice

None.

#### 6.4 Reference to other sections

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

### **SECTION 7: Handling and Storage**

#### 7.1 Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation, including appropriate local extraction to ensure occupation



# Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH)

#### www.siriusmarine.co.uk

exposure limits are not exceeded. Avoid breathing fumes/vapour. Avoid contact with skin and eyes. Use intrinsically sound equipment. Wear suitable personal protective equipment (See Section 8).

Do not eat, drink or smoke in the vicinity of the product. Wash exposed skin after use. Contaminated clothing should be thoroughly cleaned or disposed of as hazardous waste.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Keep from direct sunlight. Store locked up. Store only in the original container. Store in a cool, well ventilated place. Maximum handling temperature: 50°C. Empty containers retain product residue and can be hazardous.

Keep away from oxidising agents.

#### 7.3 Specific end uses(s)

Liquid fuel additive.

#### **SECTION 8: Exposure Controls/Personal Protection**

#### 8.1 Control parameters

#### Workplace exposure limits

Source: EH40/2005.

Substance	CAS No.	LTEL (8 hr TWA)		STEL (15 min)		Comments
Substance	CAS NO.	ppm	mg/m³	ppm	mg/m³	Comments
Xylene, o-,m-,p- or mixed isomers	1330-20-7	50	220	100	441	Sk, BMGV
Trimethylbenzenes, all isomers or mixtures	25551-13-7	25	125	-	-	-

Sk: Can be absorbed through the skin. BMGV: Biological monitoring guidance value.

#### **Biological monitoring guidance values (BMGVs)**

Source: EH40/2005.

Substance	Biological monitoring guidance values	Sampling time
Xylene, o-, m-, p- or mixed isomers	650 mmol methyl hippuric acid/mol creatinine in urine	Post shift



# According to Regulation (EC) No. 1907/2006 (REACH)

#### www.siriusmarine.co.uk

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction to ensure occupation exposure limits are not exceeded.

8.2.2 Personal protection

**Eye protection:** Goggles giving complete protection to eyes. (EN 166)

Skin protection:

**Hand protection:** Chemical resistant gloves. (EN 374).

Other: Long sleeve protective clothing. Plastic apron. Rubber

boots.

Respiratory protection: In the case of insufficient ventilation, wear suitable

respiratory equipment. (BS EN 14387:2004+A1)

Thermal hazards: Wear suitable temperature resistant gloves and

protective clothing if the product is heated.

#### 8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.

### **SECTION 9: Physical and Chemical Properties**

#### 9.1 Information on basic physical and chemical properties

Appearance: Brown liquid.

Odour: Aromatic.

Odour threshold:

pH:

Not available.

Melting/freezing point::

Not available.

Not available.

Not available.

185 - 215°C

Flash point: > 65°C (Closed cup)

**Evaporation rate:**Not available. **Flammability (solid; gas):**Not applicable.

**Upper/lower flammability or explosive limits:** Approximately 0.7 – 6.0%

Vapour pressure:Not available.Vapour density:Not available.



# According to Regulation (EC) No. 1907/2006 (REACH)

#### www.siriusmarine.co.uk

**Relative density:** 0.81 - 0.98 (Water = 1)

Solubility(ies): Immiscible in water.

Miscible in aromatic solvents.

Partition coefficient: n-octanol/water: Not available.

Auto-ignition temperature: Not available.

**Decomposition temperature:** Not available.

Viscosity: 10 – 50 cSt (40°C) (Kinematic)

**Explosive properties:** Not explosive. Vapour may form explosive mixture with

air.

Oxidising properties: Not oxidising.

9.2 Other information

None.

### **SECTION 10: Stability and Reactivity**

**10.1 Reactivity** Reacts with oxidising agents.

**10.2 Chemical stability** Stable under normal conditions.

**10.3** Possibility of hazardous reactions No hazardous reactions expected during normal use.

**10.4 Conditions to avoid**Keep away from sources of ignition, hot surfaces and

direct sunlight. Contact with incompatible materials.

**10.5** Incompatible materials Oxidising agents.

**10.6** Hazardous decomposition products Combustion may liberate toxic fumes: Carbon monoxide,

carbon dioxide, various hydrocarbons and nitrogen

oxides.

### **SECTION 11: Toxicological Information**

#### 11.1 Information on toxicological effects

Acute toxicity Harmful if swallowed. Harmful in contact with skin.

Harmful by inhalation.

No data available on the mixture.

**Skin corrosion/irritation**Causes skin irritation.



### Safety Data Sheet

#### According to Regulation (EC) No. 1907/2006 (REACH)

Serious eye damage/irritation Causes serious eye irritation.

Skin sensitisation No evidence of skin sensitisation.

Respiratory sensitisation No evidence of respiratory sensitisation.

Germ cell mutagenicity No evidence of mutagenicity.

Carcinogenicity Suspected of causing cancer.

Reproductive toxicity No evidence of reproductive toxicity.

**Specific Target Organ Toxicity – single** 

exposure

May cause irritation from prolonged exposure.

Specific Target Organ Toxicity -

repeated exposure

Based on the available data, the classification criteria

are not met.

**Aspiration hazard** May be fatal if swallowed and enters airways. Risk of

aspiration into lungs resulting in chemical pneumonia.

Information on likely routes of exposure

Inhalation Harmful by inhalation.

Harmful in contact with the skin. Causes skin irritation. Skin contact

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed. May be fatal if swallowed and

enters airways. Risk of aspiration into lungs resulting in

chemical pneumonia.

and toxicological characteristics

Symptoms related to the physical, chemical Skin contact causes redness and pain. Eye contact causes watering, redness and pain. Inhalation of high concentrations of vapour may cause irritation to the respiratory tract. Ingestion may cause irritation to mouth,

throat and digestive tract. If swallowed, aspiration into

lungs may result in chemical pneumonia.

Mixture versus substance information No data available.

Other information None.



# According to Regulation (EC) No. 1907/2006 (REACH)

www.siriusmarine.co.uk

#### **SECTION 12: Ecological Information**

**12.1 Toxicity** Toxic to aquatic life with long lasting effects.

LC50 (Fish): 1 – 10 mg/l, 96 h EC50 (Daphnia): 1 – 10 mg/l, 48 h

**12.2** Persistence and degradability No data available.

**12.3** Bioaccumulative potential No data available.

**12.4 Mobility in soil** No data available.

12.5 Results of PBT and vPvB The product does not contain substances assessed to

**assessment** be PBT or vPvB.

**12.6** Other adverse effects None known.

#### **SECTION 13: Disposal Considerations**

#### 13.1 Waste treatment methods

To be disposed of as hazardous waste. Disposal should be in accordance with local, state or national legislation.

Contaminated adsorbent must be removed in sealed, plastic lined drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.

#### **SECTION 14: Transport Information**

**ADR** 

**14.1 UN Number** 3082

**14.2 UN Proper shipping name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

LIQUID, N.O.S. (contains naphthalene)

14.3 Transport hazard class(es)

14.4 Packing group

14.5 Environmental hazards Yes

**14.6 Special precautions for the user** Read SDS and supplier instructions on correct use of

the product.

ADN

**14.1 UN Number** 3082



# Safety Data Sheet

### According to Regulation (EC) No. 1907/2006 (REACH)

14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains naphthalene)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of
		the product.
RID		
		0000
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains naphthalene)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
IATA/	ICAO	
14.1	UN Number	3082
14.2	UN Proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains naphthalene)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Yes
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of the product.
IMDG		
14.1	UN Number	3082
14.2	UN Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains naphthalene)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Marine pollutant.
14.6	Special precautions for the user	Read SDS and supplier instructions on correct use of
-		the product.
14.7	Transport in bulk according to Annex II	The product is not intended to be transported in bulk.

Version: 2.0 Date: 05/02/2013

of MARPOL 73/78 and the IBC code



### Safety Data Sheet

# According to Regulation (EC) No. 1907/2006 (REACH)

#### **SECTION 15: Regulatory Information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP), Directive 67/548/EEC & Directive 1999/45/EC.

15.2 Chemical Safety Assessment

Not applicable.

#### **SECTION 16: Other Information**

#### Full text of relevant R-phrases and/or H-statements:

**Hazard Statement(s):** H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H332: Harmful if inhaled.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H319: Causes serious eye irritation. H351: Suspected of causing cancer.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects. H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects.

**Supplemental Hazard information** None. **(EU):** 

Risk phrase(s): R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin. R20/21/22: Harmful by inhalation, in contact with skin

and if swallowed.

R21/22: Harmful in contact with skin and if swallowed.

R22: Harmful if swallowed.

R34: Causes burns.

R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R40: Limited evidence of a carcinogenic effect. R50/53: Very toxic to aquatic organisms may cause



## Safety Data Sheet

# According to Regulation (EC) No. 1907/2006 (REACH)

long-term adverse effects in the aquatic environment. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52: Harmful to aquatic organisms.

R65: Harmful: may cause lung damage if swallowed.

#### **Abbreviations:**

CAS: Chemical Abstracts Service;

EINECS: European Inventory of Existing Commercial Chemical Substances

PBT: Persistent, Bioaccumulative and Toxic. vPvB: Very Persistent and Very Bioaccumulative.

#### References:

Supplier's Safety Data Sheets for ingredients
Product formulation
Approved Classification and Labelling Guide (Sixth edition)
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009
Regulation (EC) No. 1272/2008 of the European Parliament and of the council.

#### **Disclaimer:**

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE, BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM, IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

#### **Version history:**

Version: 2.0

**Issue date:** 05/02/2013

Previous Version: 1.0

Issue date of previous version: 08/11/2011

Sections changed from previous version: 1-16